

## REPORT DOCUMENTATION PAGE

AFRL-SR-BL-TR-98-

Subsequent to the completion of the report, the author is requested to provide a number of responses to the following questions. The information provided should be used to determine the need for additional data, and to determine the need for additional data. The information provided should be used to determine the need for additional data, and to determine the need for additional data.

0641

1. AGENCY USE ONLY (leave blank)		2. REPORT DATE		3. REPORT TYPE AND DATES COVERED Final 01 May 93 To 31 May 98	
4. TITLE AND SUBTITLE LOCAL SPATIO-TEMPORAL ANALYSIS IN VISION SYSTEMS:				5. FUNDING NUMBERS F49620-93-1-0307 3484/HS 61103D	
6. AUTHOR(S) W.S. GEISLER, A.C. BOVIK, D.G. ALBRECHT, J. GHOSH L.K. CORMACK, D.L. GILDEN, B.J. SUPER					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Center for Vision & Image Sciences University of Texas at Austin Mezes Hall 330 Austin TX 78712				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) AFOSR/NL 110 Duncan Avenue Room B115 Bolling AFB DC 20332-8050  Dr John F. Tangney				10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION / AVAILABILITY STATEMENT  Approved for public release; Distribution unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  This is the final progress report of the vision group at the University of Texas under support of AFOSR URI grant F49620-93-1-0307. In this report we will attempt to summarize the major accomplishments over the previous 5 years. Aim 1: to develop a mathematical model of the initial stages of visual processing (the front-end mechanisms), based upon a wide range of physiological and psychophysical data. Aim 2: To develop new methods and models of local frequency coding. Aim 3: To develop new mathematical models and computer-vision algorithms for performing complex visual tasks that are based upon local frequency coding representations. Aim 4: To develop models for human performance in complex visual tasks that build upon current understanding of the front-end mechanisms. Aim 5: To develop a computational testbed for implementing, comparing, integrating and visualizing the different models and modules developed during the project, using a massively parallel machine and graphics workstation front-end.					
14. SUBJECT TERMS  DPO QUALITY INSPECTED 1				15. NUMBER OF PAGES	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT (U)	18. SECURITY CLASSIFICATION OF THIS PAGE (U)	19. SECURITY CLASSIFICATION OF ABSTRACT (U)	20. LIMITATION OF ABSTRACT (UL)		

**Local Spatio-temporal Analysis in Vision Systems:  
Final Technical Report**

**AFOSR F49620-93-1-0307**

August 1, 1997 to May 31, 1998

**Investigators:**

W. S. Geisler  
A. C. Bovik  
D. G. Albrecht  
J. Ghosh  
L. K. Cormack  
D. L. Gilden  
B. J. Super

Mezes 330  
University of Texas at Austin  
Austin TX 78712

19980923 049

Submitted: September 1998

## Introduction

This is the final progress report of the vision group at the University of Texas under support of AFOSR URI grant F49620-93-1-0307. This year we have been operating under a no cost extension of the grant. Because a relatively small amount of funds were carried over into this year, progress on the specific aims of the proposal were less this year than in previous years. In this report we will attempt to summarize the major accomplishments over the previous 5 years.

Before presenting the technical details, we mention several related developments that have been a direct result of the URI grant.

- (a) The interdisciplinary Center for Vision and Image Sciences (CVIS), was formed as a direct consequence of the URI grant. The Center was awarded renovated space (in addition to the existing research space of the Center faculty). Further, construction of a new \$42M Psychology building will begin shortly. In the current architectural plans, the Center has been given approximately 1000 sq. ft. of very nice space (in addition to the research space for the Center faculty). The URI grant has also served as a key factor in the acquisition of additional research space and equipment from the Departments of Psychology and Electrical and Computer Engineering.
- (b) A number of research grants from NIH and DOD have been submitted through the Center and are now being administered through the Center.
- (c) The University of Texas has provided some funds to the Center for equipment, and for administrative staff, in the form of returned overhead.
- (d) The Center has expanded to include new faculty (Todd Maddox and Brian Evans), and has attracted a visiting scholar (Bruce Henning from University of Oxford) who was at the Center this year.
- (e) The URI grant has fostered increased interactions between faculty and students in the Department of Psychology, the Department of Electrical and Computer Engineering, and the Biomedical Engineering Program. The nature and depth of some of these interactions is apparent in this progress report.

## Objectives

**Aim 1:** *To develop a mathematical model of the initial stages of visual processing (the front-end mechanisms), based upon a wide range of physiological and psychophysical data.*

**Aim 2:** *To develop new methods and models of local frequency coding.*

**Aim 3:** *To develop new mathematical models and computer-vision algorithms for performing complex visual tasks that are based upon local frequency coding representations.*

**Aim 4:** *To develop models for human performance in complex visual tasks that build upon current understanding of the front-end mechanisms.*

**Aim 5:** *To develop a computational testbed for implementing, comparing, integrating and visualizing the different models and modules developed during the project, using a massively parallel machine and graphics workstation front-end.*

## Accomplishments / New Findings

Publications, submitted papers, conference presentations and technical reports are listed at the end of the progress report. Copies of some of the relevant written material since the last progress report are appended.

**I. Aim 1:** *To develop a mathematical model of the initial stages of visual processing (the front-end mechanisms), based upon a wide range of physiological and psychophysical data.*

### A. Albrecht's Laboratory

During the project period Albrecht, Geisler and students have made very substantial progress in developing a general model of single neuron responses in the primary visual cortex of the macaque monkey. The model contains four major components: contrast gain, linear filter, expansive exponent, internal noise. This combination of linear and nonlinear components, arranged in a particular sequence, accounts for much single unit data and reveals many interesting and unexpected aspects of how visual cortex neurons transmit, extract and encode information about objects in the environment. This model has been widely cited and tested by researchers in other laboratories.

Albrecht, Geisler and students have also developed important new methods for characterizing the information processing properties of single neurons and populations of single neurons. Specifically, they developed (for the first time) a precise Bayesian method (the *descriptive function method*) for measuring the feature identification performance of single neurons, and the discrimination performance of entire populations of single neurons.

Albrecht, Geisler and students have made many new quantitative measurements of the responses of single neurons in the primary visual cortex of the macaque monkey. The studies included precise quantitative measurements of tuning functions along various stimulus dimensions, of response noise characteristics, of the effect of contrast on spatio-temporal phase, and of the effects of naturalistic temporal stimulus presentation. All of these studies revealed important general systematic properties of cortical neurons which have made important contributions to the development of the general model.

A readable summary of the work carried out by Albrecht and Geisler under the AFOSR URI grant is given in a chapter which will appear in the *Handbook of Cognition and Perception* (enclosed).

### **B. Cormack's Laboratory**

During the project period Cormack and students have made significant progress toward understanding of the effects of early filtering on binocular vision and stereopsis. Progress was made through both human behavioral studies and computational modeling. Areas in which the most progress was made include the theoretical efficiency of stereopsis, the influence of spatial frequency channeling on stereopsis, and the nature of depth encoding. Estimates of the efficiency of stereopsis were established using an ideal observer applied to the binocular random noise stimuli. These experiments established estimates of the limiting sampling density and information capacity of the binocular visual system. More surprisingly, they revealed that early binocular integrating areas are not fixed, but seem to be able to adjust in space-time to achieve maximum efficiency for the task at hand.

### **C. Geisler's Laboratory**

During the project period, Geisler and students have made substantial progress in developing a general model of human pattern detection and a general model of pattern discrimination. A key feature of the models is that they are strongly constrained by the known anatomy and physiology of the human/primate visual system. Specifically, the models consist largely of anatomically and physiologically determined mechanisms, followed by an optimal (Bayesian) decision rule. Thus, the models have almost no free parameters. By being closely tied to the anatomy and physiology of the primate visual system, the models provide a stronger link between psychophysics and neurophysiology than previous pattern vision models, and they have an excellent chance of being able to predict performance under a wider range of novel circumstances.

There are two versions of the model. The first version (which is designed for detection) contains the following components: (1) the optics of the eye (based on objective measurements in humans), (2) the human ganglion cell distribution across the retina (based on the anatomical measurements in humans), (3) the

macaque ganglion-cell receptive-field shapes (based upon the electrophysiological measurements), (4) the macaque cortical contrast-response nonlinearities (based upon the electrophysiological measurements), (5) the macaque cortical neural noise characteristics (based upon the electrophysiological measurements), (6) a (maximum-likelihood) decision rule which optimally pools the responses of all the neurons. This model predicts a range of psychophysical data quite accurately, suggesting that the anatomical and physiological mechanisms included in the model are the ones most responsible for determining human detection performance under steady background conditions.

The second version of the model (which we call a *neuron sampling model*) is similar to the first, except for the inclusion of cortical receptive field shapes. Our approach has a new unique feature not contained in other spatial vision models. Rather than representing cortical spatial coding as a small set of spatial-frequency and orientation-tuned channels (i.e., just a few different receptive field shapes), we take into account the true heterogeneity of the cortex. Specifically, we use actual electrophysiologically measured distributions (histograms) for the center spatial frequency, center orientation, spatial-frequency bandwidth, orientation bandwidth, etc. to construct a truly heterogeneous (and hence realistic) sample of cortical neurons. Because there is something on the order of 100 times as many primary cortex neurons as ganglion cells, it is not feasible to build a model which represents every cortical neuron. However, by randomly sampling from the measured distributions, we can create a large, statistically-accurate sample (e.g., several hundred thousand neurons). The predictions for such a sample match that for a complete set of neurons, except for a scale factor on threshold (more precisely, a scale factor on  $d'$ ). This model generalizes the first version by allowing predictions for pattern discrimination. The model predicts the contrast discrimination functions and spatial frequency discrimination functions reasonably well (without free parameters). An interesting exception is that the model does not predict the "dipper effect" seen in contrast discrimination functions. These results point to the importance of the heterogeneity of the cortex in determining human discrimination performance, and that the dipper effect is probably due to mechanisms beyond primary visual cortex (contrary to the current viewpoint).

## II. Aim 2: Develop new methods and models of local frequency coding.

### A. Bovik's Laboratory

Bovik and students have developed the general theory and computation of very general *image modulation models*, whereby image contrast and phase structures in image data are modeled as amplitude- and frequency-modulated (AM & FM) sinusoidal functions, and especially, as sums of such functions. The approach broadly generalizes the sinusoidal models commonly used both in studies of biological visual perception (e.g., the spatial-frequency channel models, and the so-called "energy" models of spatio-temporal vision), and also in engineering analysis of digitized images (e.g., the Discrete Fourier Transform). They have shown the new image model to be quite powerful for a variety of important applications, including analyzing nonstationary image structures; segmenting

nonstationary textured images; computing object shape from monocular images; computing depth from binocular images by stereoscopic matching of image modulations; image compression via the "AM-FM Transform," and classification and recognition of digitized fingerprints via AM-FM modeling. They have also successfully fused the AM-FM model with wavelet-based methods for modulation extraction, and we have proposed the AM-FM model as a possible mechanism for local/global modeling of visual data in biological vision systems.

This work and its offshoots has resulted in numerous high-profile image processing journal publications, and it has resulted in the graduation of a several PhD students working on AM-FM problems: Joseph P. Havlicek, currently Assistant Professor at the University of Oklahoma, Norman, OK; Boaz S. Super, currently Assistant Professor at the University of Illinois, Chicago; Terry Chen, currently Research Scientist at the Chung-Shan Institute of Science and Technology in Taiwan; Dong Wei, currently Assistant Professor at Drexel University in Philadelphia, PA; and Marios Pattichis, currently Assistant Professor at Washington State University, Pullman, WA.

**III. Aim 3:** Develop new mathematical models and computer-vision algorithms for performing complex visual tasks that are based upon local frequency coding representations.

#### ***A. Bovik's Laboratory***

**FOVEA:** Foveated, Fixating Stereo Active Vision System.

Bovik and students have successfully developed the theory, algorithms, hardware realization, and benchmark testing of a unique, state-of-the-art foveated and fixating active stereoscopic vision system with computer-controlled vergence, baseline adjustment, pan, tilt, and focus control. The successful implementation of a graded resolution hierarchy emanating from a central fovea into a truly participatory active vision system (which is a first) has made it possible to place the burden of obtaining detailed, high-resolution scene information on the design of fixation, vergence and focusing strategies. In FOVEA, dense 3-D scene representations are obtained by introducing multiple fixation points, which are subsequently integrated, making computation efficient and well-posed. Alternative approaches which are based upon massive, single-frame number-crunching are vastly less efficient and are ill-posed.

Construction of the FOVEA platform entailed the design and development of a foveated active vision system that is fully software-controllable. FOVEA allows the expert program to combine hardware and software protocols for computer feedback-controlled variable baseline vergent stereo, and for lens parameter control (including zoom, software foveation, depth-from-focus, and dynamic aperture control). They have designed and implemented software foveation protocols, whereby the degree of foveation is controlled according to the scene characteristics; they designed methods for estimating 3-D range from defocus information by using active focus control to directly estimate the depth of points or regions in a scene; they developed freeform visual fixation algorithms whereby the

cameras are directed towards regions of interest combined with a semi-random fixation strategy that explores the entirety of the scene with particular emphasis on high-information features; they developed a foveation-driven stereo camera vergence strategy which is ideally suited for efficiently computing depth vergent (non-parallel) cameras, using the observation that the tradeoff between matching complexity (highest near the periphery in a vergent system) and depth resolution (lowest near the periphery in a foveated system) be made explicit in a natural way; and they demonstrated all of these many facets of work in a fully functional, on-line series of demonstrations of FOVEA that effectively highlight FOVEA's provocative capabilities and potential for future development and application.

The results of this work have been published in a series of high-profile journal papers and the work has resulted in two PhD dissertations being completed: Changhoon Yim, currently a Research Engineer at David Sarnoff Research Center, Princeton, NJ, and William Klarquist, currently a Research Engineer at SAIC, Denver Colorado.

### ***B. Ghosh's Laboratory***

Ghosh and students have made considerable progress working out the implications of artificial foveated vision for a variety of engineering applications. These studies also quantified the computational implications and advantages of foveated processing. Major results include emergence of innovative non-uniform resolution techniques for pattern analysis and classification, and a detailed implementation of an artificial foveated system using retinal and ganglion sampling/receptive field data from primates, and showing its impact on different imagery, particularly those involving texture segregation.

Equally important work has involved the investigation of neural network approaches to various pattern recognition and learning processes related to human and artificial vision. Fundamental contributions were made to the theory and applications of localized receptive field based networks, and to the theory of network ensembles for better and more robust pattern recognition, leading to several full-length journal papers.

### ***C. Super's Laboratory***

During the project period, Super developed models to capture the relationship between the local spatial frequency decompositions of surface patterns and their corresponding image patterns, as a function of the surface geometry and the projection process. These models were successfully used to develop algorithms for recovery of 3D surface orientation and shape from analysis of image texture ("shape-from-texture"). A variation of the model that included sampling effects was used for simultaneous recovery of surface depth and orientation from stereopsis. The stereo algorithm was designed to operate under conditions, such as wide baseline and short object distance, that are considered difficult for traditional stereo algorithms because of the large inter-image distortions



induced. The stereo model was also used to study the interaction of photoreceptor mosaic sampling effects with stereo viewing geometry in the human visual system's binocular apparatus.

**IV. Aim 4:** *Develop models for human performance in complex visual tasks that build upon current understanding of the front-end mechanisms.*

#### **A. Cormack's Laboratory**

Cormack and students completed a series of experiments on the influence of early spatial frequency filtering in stereovision. They established the existence of some very interesting spatial frequency interactions in the binocular visual system. In short, it was revealed that the binocular visual system takes advantage of information present in different spatial frequency channels to resolve ambiguities that arise in matching the two eyes' images. A computational model was developed that accounted for the data and predicted some novel results.

A series of experiments was also done in order to investigate the manner in which the depth signal is encoded by the visual system beyond the site of binocular combination. These experiments revealed a critical dependence on the temporal aspects of the stimuli, and indicate that there may be two parallel systems for encoding depth, one with very transient temporal properties and another that is more sluggish. A computational model of depth encoding with these properties was developed and predictions from the model are being tested in ongoing experiments.

#### **B. Geisler's Laboratory**

During the project period Geisler and students developed a theoretical approach and an experimental method for assessing (and hence isolating) the role of low-level factors in complex tasks. The method involves comparing simple-discrimination performance and visual search performance for the same stimuli. Analysis of the results showed that much of the variation in (multiple fixation) search time was predictable from the discrimination data, suggesting that low-level factors often play a dominant role in limiting search performance. They also developed a signal-detection model which demonstrates how current psychophysical models of visual discrimination might be generalized in order to obtain a quantitative theory that can predict visual search performance under a wide range of stimulus conditions. A new real-time method of controlling the information across the visual field during active search was inspired by this work. Specifically, under another AFOSR proposal Geisler and students developed real-time software that runs on a PC and can be used to dynamically modulate the spatial frequency content of arbitrary static or video imagery contingent upon eye position measured with an eye tracker. This software has great potential for the study of visual search.

In a related line of research, Geisler, Super and students have explored how local spatial information extracted by the primary visual cortex is combined to find the

spatial structure that exists in 2-D images (an ability that is very well-developed in the human visual system). Geisler, Super and students have developed, and tested in psychophysical experiments, a computational model that incorporates most of the known grouping rules within a single coherent framework. This model addresses many aspects of perceptual organization not addressed by previous models.

### ***C. Gilden's Laboratory***

During the project period Gilden and students have been involved in two main areas of research. The first concerns the nature of the fluctuations in performance that occur in various perceptual and cognitive tasks (mental rotation, lexical decision, parallel visual search, and serial visual search). They find that a substantial fraction of the residual variability, and this generally exceeds 90% of the total variance in individual subjects, is described by a  $1/f$  noise distribution.  $1/f$  noise refers to a signal that has a power spectrum that is inversely proportional to frequency and is thought to be produced in self-organizing critical systems. These findings may have a wide impact upon the development of models for perceptual estimation in many stimulus domains.

The second area of research concerns motion perception. Gilden has developed a theory of motion perception based on mathematical and visual constraints on the formation of frames of reference. One implication of the theory is that if and only if a motion field can be fully represented by diagonal energy in space-time can it be processed preattentively. Only translation fields satisfy this requirement. Rotation fields, for example, require spatial distinctions with respect to the axis of rotation, in addition to the specification of local speed; e.g., clockwise rotation has the upper part of the field moving right and the lower part of the field moving left. For homogeneous translation fields there is no local specification of spatial concepts such as upper and lower. Gilden has tested the theory in a large series of experiments by measuring memory and search performance for translating, rotating, and diverging (expanding or contracting) stimuli. The theory is largely supported although there are some interesting twists. The major results are as follows: (1) There is good memory for speed of translation independent of speed, but there is poor memory for rotational speed except for slower rotations. (2) There is good memory for direction of translation and divergence, but very poor memory for direction of rotation so long as the axis of rotation is contained within the object. (3) If the rotation axis is external to the object then there is significant memory for clockwise rotations, but very poor memory for counterclockwise rotations. (4) In careful search experiments it appears that rotation direction is subject to a limited capacity parallel search, whereas translation direction is more characteristics of unlimited capacity parallel search.

### ***D. Super's Laboratory***

Super and Geisler (1) developed a theoretical framework for perceptual organization, (2) carried out a series of experiments on human subjects to quantitatively measure perceptual grouping behavior in the human visual system (HVS), and (3) developed a computational model of perceptual

grouping behavior in the HVS. Additionally, Super has developed a preliminary architecture for multi-level grouping (grouping which involves interactions across levels in the grouping hierarchy) in computer vision systems. This research led to a new method for cluster selection in hierarchical cluster analysis in the field of pattern recognition.

**V. Aim 5:** Develop a computational testbed for implementing, comparing, integrating and visualizing the different models and modules developed during the project, using a massively parallel machine and graphics workstation front-end.

#### ***A. Ghosh's Laboratory***

Ghosh and students have completed work on forming a suite of computational vision algorithms as well as programs related to modeling the human visual system. These algorithms have been implemented on the 4K processor MasPar MP-1, and used for various empirical studies. For example, based on the retinal filter of Geisler and current knowledge of ganglion sampling and receptive field parameters, they have done extensive studies on texture discrimination using a foveated front-end model of the human retina.

### **Personnel Supported**

#### ***Principal Investigators***

Wilson Geisler  
 Alan Bovik  
 Duane Albrecht  
 Joydeep Ghosh  
 David Gilden  
 Lawrence Cormack  
 Boaz Super

#### ***Technical Support Personnel***

Carl Creeger  
 Larry Stern  
 Alison Crane Tannenbaum

#### ***Administrative Support Personnel***

Christine Fry

#### ***Direct Research Personnel***

##### ***Students***

Kurt Bollacker  
 Joseph Havlicek (graduated with Ph.D)  
 Viral Kadakia  
 William Klarquist (graduated with Ph.D)  
 Turker Kuyel

Xiaonong Li  
 David Landers  
 Hung-Ta Pai  
 Sangho Park  
 Marios Pattichis  
 Christy Price  
 Vishwanath Ramamurthy  
 Bryan Stiles  
 Tom Thornton  
 Dong Wei  
 Changhoon Yim (graduated with Ph.D)  
 Robert Frazor  
 Caden Schafer  
 Cecily Anders  
 Terry Chen (graduated with PhD)  
 Dave Harding  
 Jeff Wehnes  
 Kartick Subramanian (summer 1997)

## PUBLICATIONS

Publications marked \* are appended.

### 1993 Publications

1. Albrecht, D. G. and Geisler, W. S. (1993). Visual cortex neurons in monkey and cat: Contrast response nonlinearities and stimulus selectivity. In: T. Lawton (Ed.), *Computational Vision Based On Neurobiology, SPIE Proceedings, 2054*, 12-31.
2. Cormack, L. K., Stevenson, S. B. and Schor, C. M. (1993). Disparity-tuned channels of the human visual system. *Visual Neuroscience*, 10, 585-596.

### 1993 Conference Presentations / Talks / Technical Reports

3. Cormack, L. K. (1993, May). Interocular correlation detection with oriented contours. *Annual Meeting of the Association for Research in Vision and Ophthalmology*.
4. Cormack, L. K. (1993, September). Binocular matching and stereopsis. *University of Houston*.
5. Geisler, W. S. (1993, July). Low level and high level factors in visual performance. *University of Minnesota*.

6. Geisler, W. S. (1993, August). Sequential analysis of visual performance. *U. S. Army Research Labs, Aberdeen Proving Ground, MD.*
7. Geisler, W. S. (1993, November). A model of visual discrimination performance. *The Rockefeller University.*
8. Gilden, D. L., Hiris, E., and Blake, R. (1993, May). Motion coherence is perceived as information entropy. *Annual Meeting of the Association for Research in Vision and Ophthalmology.*
9. Super, B. J. and Bovik, A. C. (1993). Shape-from-Texture using local spectral moments. *Technical Report UT-CVIS-TR-93-001, Austin, Texas: Center for Vision and Image Sciences.*
10. Super, B. J., Bovik, A. C., and Geisler, W. S. (1993, May). A model of shape from texture using second-order moments of local spatial-frequency spectra. *Annual meeting of the Association for Research in Vision and Ophthalmology.*

#### 1994 Publications

11. Chakravarthy, S. V. and Ghosh, J. (1994). Scale based clustering using a radial basis function networks, *Proceedings. IEEE International Conference on Neural Networks*, 7, 897-902.
12. Chen, T. -Y., Bovik, A. C. and Super, B. J. (1994). Multiscale stereopsis via Gabor filter phase response. *IEEE International Conference on Systems, Man, and Cybernetics. Humans, Information and Technology*. 1, 55-60
13. Cormack, L. K., Stevenson, S. B. and Schor, C. M. (1994). An upper limit to the binocular combination of stimuli. *Vision Research*, 34, 2599-2608.
14. Ghosh, J. and Chakravarthy, S. V. (1994). The rapid kernel classifier: A link between the self-organizing feature map and the radial basis function network. *Journal of Intelligent Material Systems and Structures, (special issue on neural networks)*, 5, 211-219.
15. Ghosh, J. and Tumer, K. (1994). Structural Adaptation and generalization in supervised feedforward networks. *Journal of Artificial Neural Networks*, 1(4), 431-458.
16. Havlicek, J. P. and Bovik, A. C. (1994). Multi-component AM-FM image models and wavelet-based demodulation with component tracking. *IEEE International Conference on Image Processing*, 1, 41-5.

17. Klarquist, W. N. and Bovik, A. C. (1994). The Texas active vision testbed, *IEEE International Conference on Systems, Man, and Cybernetics*, 2, 1381-6.
18. Maragos, P. and Bovik, A. C. (1994). Demodulation of images Modeled by amplitude-frequency modulations using multidimensional energy separation, *IEEE International Conference on Image Processing*, 3, 421-5.
19. Stevenson, S. B., Cormack, L. K. & Schor, C. M. (1994). The effect of stimulus contrast and interocular correlation on disparity vergence. *Vision Research*, 34, 383-396.
20. Tumer, K. and Ghosh, J. (1994). Sequence recognition by input anticipation. *Proceedings. IEA/AIE'94*, Austin, Texas.
21. Tumer, K. and Ghosh, J. (1994). A framework for estimating performance improvements in hybrid pattern classifiers. *World Congress on Neural Networks*, San Diego, California, pp.III: 220-225.
22. Yim, C., Klarquist, W. N. and Bovik, A. C. (1994). Multiresolution feature extraction based on multifrequency decomposition. *IEEE International Conference on Systems, Man, and Cybernetics*, San Antonio, Texas.

#### **1994 Conference Presentations / Talks / Technical Reports**

23. Balasubramanyam, P. (1994, May). Motion perception from local motion and disparity measurements. *Annual meeting of the Association for Research in Vision and Ophthalmology*.
24. Chen, T-Y, Bovik, A.C. and Super, B.J. (1994). Multiscale stereopsis via Gabor filter phase response. *Proceedings of the IEEE International Conference on Systems, Man, and Cybernetics*, San Antonio, Texas, pp. 55-60.
25. Chen, T.-Y., Klarquist, W. N. and Bovik, A. C. (1994, April). Stereo vision using Gabor wavelets. *IEEE Southwest Symposium on Image Analysis and Interpretation*.
26. Cormack, L. K. and Landers, D. D. (1994, May). The efficiency of binocular matching. *Annual Meeting of the Association for Research in Vision and Ophthalmology*.
27. Geisler, W. S. (1994, March). Model of single neuron responses in primary visual cortex. *School of Optometry, University of Houston*.

28. Geisler, W. S. (1994, April). Optical and retinal factors in spatial vision and adaptation. *University of Texas Health Sciences Center, Houston.*
29. Geisler, W. S. (1994, May). Optical and retinal factors in spatial vision and adaptation. *Annual meeting of the Association for Research in Vision and Ophthalmology.*
30. Geisler, W. S. , and Klarquist, W. N. (1994). Maximum-likelihood method for image deblurring and depth-from-defocus. *Technical Report UT-CVIS-TR-94-008, Austin, Texas: Center for Vision and Image Sciences.*
31. Ghosh, J. (1994, June). Scale-based clustering using a radial basis function network. *IEEE International Conference on Neural Networks.*
32. Gilden, D. L. (1994, May). Streaky performance in visual psychophysics. *Annual meeting of the Association for Research in Vision and Ophthalmology.*
33. Gilden, D. L., Thornton, T. and Mallon, M. W. (1994). Noise in the production of spatial and temporal intervals. *Annual meeting of the Psychonomic Society.*
34. Hahn, L. W. and Geisler, W. S. (1994, May). Local light-adaptation mechanisms in grating adaptation. *Annual meeting of the Association for Research in Vision and Ophthalmology.*
35. Kortum, P.T. and Geisler, W. S. (1994, May). Light adaptation mechanisms in spatial target detection. *Annual meeting of the Association for Research in Vision and Ophthalmology.*
36. Super, B. J. (1994). Patch matching and stereopsis in a general stereo viewing geometry. *Center for Vision and Image Sciences (CVIS) Seminar Talk, University of Texas at Austin, December 12, 1994.*
37. Super, B. J. and Bovik, A. C. (1994). Planar surface orientation from texture spatial frequencies. *Technical Report UT-CVIS-TR-94-001, Austin Texas: Center for Vision and Image Sciences.*
38. Tumer, K. (1994, June). Sequence recognition by input anticipation. *IEA/AIE.*
39. Yim, C and Bovik, A. C. (1994, April).. Vergence control using hierarchical image structure. *IEEE Southwest Symposium on Image Analysis and Interpretation*

## 1995 Publications

40. Albrecht, D.G. (1995). Visual cortex neurons in monkey and cat: Effect of contrast on the spatial and temporal phase transfer functions. *Visual Neuroscience*, 12, 1191-1210.
41. Chen, T.-Y. and Bovik, A.C. (1995). Stereo disparity from multiscale processing of local image phase. *IEEE International Symposium on Computer Vision*, Coral Gables, Florida.
42. Geisler, W. S. and Albrecht, D. G. (1995). Bayesian analysis of identification performance in monkey visual cortex: Nonlinear mechanisms and stimulus certainty. *Vision Research*, 35, 2723-2730.
43. Geisler, W. S. and Banks, M. S. (1995). Visual Performance. In: *Handbook of Optics*. New York: McGraw-Hill.
44. Geisler, W. S. and Chou, K. L. (1995). Separation of low-level and high-level factors in complex tasks: Visual search. *Psychological Review*, 102, 356-378.
45. Gilden, D. L., Thornton, T. and Mallon, M. W. (1995). 1/f noise in human cognition. *Science*, 267, 1837-1839.
46. Ghosh, J. (1994). Presented: Scale based clustering using a radial basis function network. (invited talk) at the *Proceedings of the IEEE International Conference on Neural Networks*, Orlando, Florida.
47. Hahn, L. and Geisler, W. S. (1995). Adaptation mechanisms in spatial vision I: Bleaches and backgrounds. *Vision Research*, 35, 1585-1594.
48. Havlicek, J.P., Bovik, A.C., Desai, M.D. and Harding, D.S. (1995). The discrete quasi-eigenfunction approximation. *International Conference on Digital Signal Processing*, Limassol, Cyprus.
49. Havlicek, J.P., Harding, D.S. and Bovik, A.C. (1995). Multi-component signal demodulation and reconstruction using AM-FM models. *IEEE Workshop on Nonlinear Digital Signal Processing*, Neos Marmaras-Haldiki, Greece.
50. Havlicek, J.P., Harding, D.S. and Bovik, A.C. (1995). Reconstruction from the multi-component AM-FM image representation. *IEEE International Conference on Image Processing*, Washington, DC.
51. Klarquist, W.N. (1995). FOVEA: A foveated vergent active stereo vision system for dynamic three-dimensional scene recovery. PhD. Dissertation, The University of Texas at Austin, Austin, Texas.



52. Klarquist, W.N. , Geisler, W.S. and Bovik, A.C. (1995). Maximum-likelihood depth-from-defocus for active vision. *IEEE International Conference on Intelligent Robots and Systems*, Pittsburgh, Pennsylvania.
53. Kortum, P. T. and Geisler, W. S. (1995). Adaptation mechanisms in spatial vision II: Flash thresholds and background adaptation. *Vision Research*, 35, 1595-1609.
54. Kuyel, T. and Ghosh, J. (1995). A fast space localized computation of the outputs of a Gabor Filter bank. *Proceedings: IASTED Conference on Signal and Image Processing (SIP-95.)*, Las Vegas.
55. Maragos, P. and Bovik, A.C. (1995). Image demodulation using multidimensional energy separation. *Journal of the Optical Society of America*, 12 (9), 1867-1876.
56. Pattichis, M.S. and Bovik, A.C. (1995). A nonlinear fluid model for describing frequency modulation of image orientations. *IEEE Workshop on Nonlinear Digital Signal Processing*, Neos Marmaras-Haldiki, Greece.
57. Pattichis, M.S. and Bovik, A.C. (1995). Multidimensional frequency modulation in texture images. *International Conference on Digital Signal Processing*, Limassol, Cyprus.
58. Shin, Y. and Ghosh, J. (1995). Ridge polynomial networks. *IEEE Trans. Neural Networks*, 6 (3), 610-622.
59. Stiles, B. W. and Ghosh, J. (1995). Habituation based neural classifiers for spatio-temporal signals. *Proceedings: ICASSP-95*, Detroit, MI.
60. Super, B. J. and Bovik, A. C. (1995). Shape from texture using local spectral moments. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, PAMI-17 (4), 333-343.
61. Super, B. J. and Bovik, A. C. (1995). Planar surface orientation from texture spatial frequencies. *Pattern Recognition*, 28 (5), 729-743.
62. Tumer, K. and Ghosh, J. (1995). Order statistics combiners for neural classifiers. *Proceedings: World Congress on Neural Networks*, Washington, DC, pp.I: 31-34.
63. Tumer, K. and Ghosh, J. (1995). Limits to performance gains in combined neural classifiers. *Intelligent Engineering Systems Through Artificial Neural Networks. Vol.5. Proceedings of the Artificial Neural Networks in Engineering (ANNIE'95)*, p.p. 419-24.

### 1995 Conferences Presentations / Talks / Technical Reports

64. Arnow, T. L. and Geisler, W. S. (1995). Cycle summation of single and compound grating patterns. *Association for Research in Vision and Ophthalmology*.
65. Cormack, L.K. and Chen, T. (1995, May). Spatial channel interaction and stereoscopic processing. *Annual Meeting of the Association for Research in Vision and Ophthalmology*.
66. Geisler, W. S. (1995). Neurophysiological mechanisms of identification and discrimination. *McDonnell Summer Institute in Cognitive Neuroscience*, UC Davis.
67. Geisler, W. S. and Albrecht, D. G. (1995). Bayesian analysis of identification performance in the primate visual cortex. *Association for Research in Vision and Ophthalmology*.
68. Ghosh, J. (April, 1995). Habituation networks. (invited talk) at *SPIE Conference on Applications and Science of Artificial Neural Networks IV*, Orlando, FL.
69. Gilden, D. L. and Price, C. (1995). Determinants of memory for motion. *Annual meeting of the Association for Research in Vision and Ophthalmology*.
70. Landers, D. D. and Cormack, L. K. (1995, May). Reaction time evidence for disparity segregation without qualitative pooling. *Annual Meeting of the Association for Research in Vision and Ophthalmology*.
71. Seay, C. A. and Geisler, W. S. (1995). Signal-detection-theory analysis of contrast matching and discrimination. *Association for Research in Vision and Ophthalmology*.
72. Stiles, B. W. (1995, May). Habituation based neural classifiers for spatio-temporal signals. *ICASSP-95*, Detroit, MI.
73. Super, B. J. (1995). Perceptual organization of two-dimensional images. *Center for Vision and Image Sciences (CVIS) Seminar Talk*, University of Texas at Austin, November 17, 1995.
74. Super, B. J. and Klarquist, W. N. (1994, November, 1995, Revised). Patch matching and stereopsis in a general stereo viewing geometry. *Technical Report UT-CVIS-TR-94-006*, Austin, Texas: Center for Vision and Image Sciences.
75. Super, B. J. and Klarquist, W. N. (1995). Patch matching and stereopsis in a general stereo viewing geometry, *Proceedings of the*

*International Conference on Digital Signal Processing*, pp. 500-505, Limassol, Cyprus.

76. Super, B. J. (1995, May). Inter-image metric deformation and sampling in human binocular vision. *Annual meeting of the Association for Research in Vision and Ophthalmology*, (ARVO) Ft. Lauderdale, FL.
77. Tumer, K. (1994, May). Sequence recognition by input anticipation. *IEA/AIE'94*, Austin, TX.
78. Tumer, K. and Ghosh, J. (1995, April). Boundary variance reduction for improved classification through hybrid networks. *Proceedings. SPIE Conference on Applications and Science of Artificial Neural Networks IV*, SPIE Proceedings Vol. 2492, Orlando, pp. 573-585.
79. Tumer, K. and Ghosh, J. (1995, July). Order statistics combiners for neural classifiers. *Proceedings of the World Congress on Neural Networks*, Washington, DC, pp.I: 31-34.
80. Yim, C. and Bovik, A. C. (1995, November). Range segmentation using focus cues, *IEEE International Symposium on Computer Vision*, Coral Gables, FL.
81. Arnow, T. L. and Geisler, W. S. (1995). Inhomogeneous retino-cortical (IRC) model of visual detection. *Annual Meeting of the Optical Society of America*.
82. Geisler, W.S. and Albrecht, D.G. (1995). Contrast and pattern identification in primate visual cortex. *Annual Meeting of the Optical Society of America*.

### 1996 Publications

83. Amaral, J. N. and Ghosh, J. (1996). A concurrent architecture for serializable production systems. *IEEE Trans. Parallel and Distributed Systems*, 7(12), 1265-80.
84. Arnow, T. L. and Geisler, W.S. (1996). Visual detection following retinal damage: Predictions of an inhomogeneous retino-cortical model. *Human Vision and Electronic Imaging. SPIE*, 2674, 119-130.
85. Bollacker, K. and Ghosh, J. (1996). Linear feature extractors based on mutual information. *Proceedings: ICPR*, Vienna, Austria, pp. IV:720-24.
86. Bollacker, K. and Ghosh, J. (1996). Mutual information feature extractors for neural classifiers. *Proceedings of the ICNN*, Washington, DC, June 1996, pp. 1528-33.

87. Chakravarthy, S.V. and Ghosh, J. (1996). Scale-based clustering using the radial basis function network. *IEEE Transactions on Neural Networks*, 7 (5), 1250-61.
88. Cormack, L. K. and Riddle, R. B. (1996). Binocular correlation detection with oriented dynamic random-line stereograms. *Vision Research*, 36, 2303-2310.
89. Gilden, D. L. (1996). Fluctuations in the time required for elementary decisions. *Psychological Science*, 8, 296-301.
90. Ghosh, J., Chang, H.-J. and Liano, K. (In press). A macroscopic model of oscillation in ensembles of inhibitory and excitatory neurons. In *Neural Networks for Spatiotemporal Processing*, J. Dayhoff (Eds.), Lawrence Erlbaum.
91. Harding, D.S., Havlicek, J.P. and Bovik, A.C. (1996). Recent advances in multi-component AM-FM image modelling. *Ninth IEEE Signal Processing Society Workshop on Image and Multidimensional Signal Processing*, Belize City, Belize.
92. Havlicek, J. P., Harding, D. S. and Bovik, A. C. (1996). Discrete quasi-eigenfunction approximation for AM-FM image analysis. *IEEE International Conference on Image Processing*, Lausanne, Switzerland.
93. Havlicek, J. P., Harding, D. S. and Bovik, A. C. (1996). Extracting essential modulated image structure. *Thirtieth Annual Conference on Signals, Systems, and Computers*, Pacific Grove, California.
94. Havlicek, J. P., Harding, D. S. and Bovik, A. C. (1996). The multicomponent AM-FM image representation. *IEEE Transactions on Image Processing, Special Issue on Nonlinear Image Processing*, 6 (5), 1094-1100.
95. Havlicek, J.P., Pattichis, M.S., Harding, D.S., Christofides, A.C. and Bovik, A.C. (1996). AM-FM image analysis techniques. *IEEE Southwest Symposium on Image Analysis and Interpretation*, San Antonio, Texas.
96. Kortum, P.T. and Geisler, W.S. (1996). Implementation of a foveated image-coding system for bandwidth reduction of video images. *Human Vision and Electronic Imaging*. SPIE, 2657, 350-360.
97. Kuyel, T., Ghosh, J. and Geisler, W. S. (1996). A Nonparametric statistical analysis of texture segmentation performance using a foveated image preprocessing similar to the human retina. *Proceedings. IEEE SW Symposium on Image Analysis and Interpretation*, San Antonio, April 1996, pp.207-212.
98. Kuyel, T. and Ghosh, J. (1996). Multiresolution nearest neighbor (MNN) Classifier: A fast algorithm for the classification of images. *Proceedings:*

*IASTED Conference on Signal and Image Processing (SIP-96)*, Orlando, Nov. 11-14, 1996, pp. 122-125.

99. Pattichis, M.S. and Bovik, A.C. (1996). A fluid model for texture images. *Ninth IEEE Signal Processing Society Workshop on Image and Multidimensional Signal Processing*, Belize City, Belize.
100. Pattichis, M. S. and Bovik, A. C. (1996). AM-FM expansions of images. *European Signal Processing Conference*, Trieste, Italy.
101. Ramamurti, V. and Ghosh, J. (1996). Flexible modular architecture for changing environments. *Intelligent Engineering Systems Through Artificial Neural Networks*, ASME Press, 6, 5-10. (*Proceedings of ANNIE '96* St. Louis, Nov. 1996),
102. Ramamurti, V. and Ghosh, J. (1996). Advances in using hierarchical mixture of experts for signal classification. *Proceedings of the International Conference on Acoustics, Speech, and Signal Processing*, vol. 6, 3569-72.
103. Ramamurti, V. and Ghosh, J. (1996). Structural adaptation in mixture of experts. *Proceedings of the 13<sup>th</sup> International Conference on Pattern Recognition*, vol. 4, 704-8.
104. Tumer, K. and Ghosh, J. (1996). Analysis of decision boundaries in linearly combined neural classifiers. *Pattern Recognition*, 29 (2), 341-348.
105. Tumer, K. and Ghosh, J. (1996). Error correlation and error reduction in ensemble classifiers. *Connection Science*, special issue on Combining, 8, (3/4), 385-404.
106. Tumer, K. and Ghosh, J. (1996). Estimating the Bayes error rate through classifier combining. *Proceedings of the International Conference on Pattern Recognition*, Vienna, Austria, Vol. 4, 695-99.

#### **1996 Conference Presentations / Talks / Technical Reports**

107. Bollacker, K. (1996, June). Mutual information feature extractors for neural classifiers. *ICNN*, Washington, DC.
108. Geisler, W. S. and Super, B. J. (1996, July). Perceptual organization of two-dimensional patterns. *Technical Report UT-CVIS-TR-96-002*, Austin, Texas: Center for Vision and Image Sciences.
109. Geisler, W.S. and Super, B.J. (1996). Theory of perceptual organization in two-dimensional images. *Investigative Ophthalmology & Visual Science Supplement*. (ARVO) 37/3, S954.

110. Gilden, D. L. (1996). Complexity in Cognition. Presented at the 1996 meeting of the *Psychonomic Society*.
111. Gilden, D. L. (1996). Complexity of cognition. Colloquium given to the Department of Psychology, Johns Hopkins University.
112. Ghosh, J. (1996, August). Estimating the Bayes error rate through classifier combining. *International Conference on Pattern Recognition*, Vienna, Austria.
113. Ghosh, J. (1996, November). Flexible modular architecture for changing environments. *ANNIE '96 Conference*, St. Louis, Mo.
114. Ghosh, J. (1996, August). Linear feature extractors based on mutual information. *International Conference on Pattern Recognition*, Vienna, Austria.
115. Kortum, P.T. and Geisler, W.S. (1996). Search performance in natural scenes: the role of peripheral vision. *Investigative Ophthalmology & Visual Science Supplement*. (ARVO) 37/3, S297.
116. Kuyel, T. (1996, November). Multiresolution nearest neighbor (MNN) classifier: A fast algorithm for the classification of images. *IASTED Conference on Signal and Image Processing (SIP-96)*, Orlando, FL.
117. Seay, C.A. and Geisler, W.S. (1996). A neuron sampling model of spatial vision. *Investigative Ophthalmology & Visual Science Supplement*. (ARVO) 37/3, S233.
118. Super, B. J. (1996, April). A computational theory of perceptual organization. *University of Illinois at Chicago*.
119. Super, B.J. and Geisler, W.S. (1996). Interaction of similarity dimensions in perceptual organization: psychophysics and a computational model. *Investigative Ophthalmology & Visual Science Supplement*. (ARVO) 37/3, S954.

### 1997 Publications

120. Bollacker, K. and Ghosh, J. (1997). Knowledge reuse in multiple classifier systems. *Pattern Recognition Letters*, vol.18, no.11-13, p. 1385-90.
121. Bovik, A. C., Havlicek, J. P., Desai, M. D. and Harding, D. S. (1997). Limits on discrete modulated signals. *IEEE Transactions on Signal Processing*, 45 (4), 867-79.
122. Chakravarthy, S. V. and Ghosh, J. (1997). Function emulation using radial basis function networks. *Neural Networks*, 10(3), 459-78.

123. Cormack, L. K., Landers, D.D. and Ramakrishnan, S. (1997). Element density and the efficiency of binocular matching. *Journal of the Optical Society of America, A*, 14, 723-730.
- 124.\* Cormack, L. K., Stevenson, S. B. and Landers, D.D. (1997). Interactions of spatial frequency and unequal monocular contrasts in stereopsis. *Perception*, 26, 1121-1136.
- 125.\* Geisler, W.S. and Albrecht, D.G. (1997). Visual cortex neurons in monkeys and cats: Detection, discrimination, and identification. *Visual Neuroscience*, 14, 897-919.
126. Havlicek, J. P., Havlicek, J. W. and Bovik, A. C. (1997). The analytic image. *IEEE International Conference on Image Processing*, Santa Barbara, California.
127. Ghosh, J. (1997). *Neural Networks for Pattern Recognition*. Sian Ka 'an, B. Fernandez (Eds), McGraw Hill.
128. Klarquist, W. N. and Bovik, A. C. (1997). Adaptive variable baseline stereo for vergence control. *IEEE International Conference on Robotics and Automation*, Albuquerque, New Mexico.
129. Landers, D.D. and Cormack, L.K. (1997). Asymmetries and errors in perception of depth from disparity suggest a multi-component model of disparity processing. *Perception and Psychophysics*, 59, 219-231.
130. Pai, H.-T. and Bovik, A. C. (1997). Exact multi-channel blind image restoration. *IEEE Signal Processing Letters*, 4(8), 217-220.
131. Pai, H.-T., Bovik, A. C. and Evans, B. L. (1997). Multichannel blind image restoration. *Elektrik*, Special Issue on Image Processing, 5(1) 79-97.
132. Pattichis, M. S., Christodoulou, C. I., Pattichis, C. S. and Bovik, A. C. (1997). Nonstationary texture segmentation using an AM-FM model. *International Conference on Neural Networks*, Houston, Texas.
133. Super, B. J. and Klarquist, W. N. (1997). Patch-based stereo in a general binocular viewing geometry. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 19 (03), page 247-252.
134. Wei, D. and Bovik, A. C. (1997). Asymptotic convergence of biorthogonal wavelet filters. *Thirty-First Annual Asilomar Conference on Signals, Systems, and Computers*, Pacific Grove, California.
135. Wei, D. and Bovik, A. C. (1997). On asymptotic convergence of the dual filters associated with two families of biorthogonal wavelets. *IEEE Transactions on Signal Processing*, 45(12) 2928-2940.

136. Wei, D., Bovik, A. C. and Evans, B. L. (1997). Generalized coiflets. *Thirty-First Annual Conference on Signals, Systems, and Computers*, Pacific Grove, California.
137. Wei, D., Evans, B. L. and Bovik, A. C. (1997). Biorthogonal quincunx coifman wavelets. *IEEE International Conference on Image Processing*, Santa Barbara, California.
138. Wei, D., Evans, B. L. and Bovik, A. C. (1997). Loss of perfect reconstruction in multidimensional filter banks and wavelets designed via extended McClellan transformations. *IEEE Signal Processing Letters*, 4(10), 295-297.

#### **1997 Conference Presentations / Talks / Technical Reports**

139. Frazor, R.A., Albrecht, D.G., Geisler, W.S. and Crane, A.M. (1997). Response of V1 neurons during intervals similar to normal fixation. *Investigative Ophthalmology & Visual Science Supplement*. (ARVO) 38/4, S15.
140. Geisler, W.S. and Albrecht, D.G. (1997). Identification performance of neurons in monkey visual cortex for simple and complex images. *Investigative Ophthalmology & Visual Science Supplement*. (ARVO) 38/4, S734.
141. Gilden, D. L. (1997). Fluctuations in cognition. Colloquium given to the Department of Psychology, Arizona State University.
142. Gilden, D. L. (1997). Perceptual constraints on understanding dynamics. Colloquium given to the Department of Psychology, University of Virginia.
143. Gilden, D. L., Price, C. M., and Thornton, T. (1997). Visual search in motion fields. Presented at the 1997 meeting of *the Association for Research in Vision and Ophthalmology*.
144. Kuyel, T. (1997, December). Sequential resolution nearest neighbor classifier: image classification using multiple visual fixations. *IASTED International Conference on Signal and Image Processing*, New Orleans, LA.
145. Kuyel, T. (1997, December). Improving the output decision rules of neural networks using K-nearest neighbors theory. *IASTED International Conference on Signal and Image Processing*, New Orleans, LA.
- 146.\* Super, B. J. (1997, November). Detection of complex similarity-based structure. *Technical Report Vislab-97-003*. The University of Illinois at Chicago, Vision Interfaces and Systems Laboratory.



## 1998 Publications

147. Acton, S. T., Wei, D. and Bovik, A. C. (To appear). Image enhancement. *Encyclopedia of Electrical and Electronics Engineering*, J.G. Webster (Ed.), John Wiley and Sons.
148. Acton, S. T. and Bovik, A. C. (1998). Nonlinear image estimation using piecewise and local image models. *IEEE Transactions on Image Processing*, 7(7), 979-991.
149. Acton, S. T. and Bovik, A. C. (1998). Order statistics in signal and image processing. In N. Balakrishnan and C.R. Rao (Eds.), *Handbook of Statistics 17 - Order Statistics and their Applications* (pp. 603-641). North-Holland.
150. Acton, S. T. and Bovik, A. C. (To appear October ). Piecewise and local image models for regularized image restoration using cross-validation. *IEEE Transactions on Image Processing*.
151. Acton, S. T. and Bovik, A.C. (Submitted). Image segmentation by nonlinear locally monotonic reduction, *Journal of Applied Signal Processing*.
152. Bovik, A. C. and Chellappa, R. (1998, March). Image analysis and recognition. *IEEE Signal Processing Magazine*, 33-34.
153. Chen, T.-Y., Bovik A. C. and Cormack, L. C. (To appear). Stereoscopic ranging by matching image modulations. *IEEE Transactions on Image Processing*.
154. Craievich, D., Barnett, B.S. and Bovik, A. C. (Submitted). A stereo visual pattern image coding system, *Image and Vision Computing*.
155. Frazor, R.A., Albrecht, D.G., Geisler, W.S. and Crane, A.M. (Submitted). Cortical Neuron Responses to Stimuli Presented in a Temporally Naturalistic Fashion. *Visual Neuroscience*.
- 156.\* Geisler, W.S. and Albrecht, D.G. (1998). Spatial Vision. In *Handbook of Perception and Cognition*.
157. Geisler, W.S. and Albrecht, D.G. (1998). Spatial Vision. In *Encyclopedia of Psychology*.
158. Geisler, W. S. and Super, B. (1998). Perceptual organization of two-dimensional patterns. Under revision for publication in *Psychological Review*.
159. Havlicek, J. P., Bovik, A. C. and Chen, D. (To appear). AM-FM image modeling and gabor analysis. In , C.W. Chen and Y.Q. Zhang (Eds.), *Visual*

*Communications and Image Processing* Optical Engineering Series,  
Marcel Dekker, Inc.

160. Havlicek, J. P., Harding, D. S. and Bovik, A. C. (To appear). Multicomponent multidimensional signals. *Multidimensional Systems and Signal Processing*.
161. Havlicek, J. P., Harding, D. S. and Bovik, A. C. (To appear). Multidimensional quasi-eigenfunction approximations and multicomponent AM-FM models. *IEEE Transactions on Image Processing*.
162. Kite, T.D., Evans, B.L. and Bovik, A.C. (Submitted). Design and quality assessment of a fast inverse halftoning algorithm for error diffused halftones. *IEEE Transactions on Image Processing*.
163. Kite, T.D., Evans, B.L. and Bovik, A.C. (Submitted). Modeling and quality assessment of halftoning by error diffusion. *IEEE Transactions on Image Processing*.
164. Klarquist, W. N. and Bovik, A. C. (To appear). FOVEA: A foveated, multi-fixation, vergent active stereo system for dynamic three-dimensional scene recovery. *IEEE Transactions on Robotics and Automation*.
165. Lee, S. and Bovik, A. C. (Submitted). Real-time optimal rate control for foveated video coding. *IEEE Transactions on Image Processing*.
166. Lee, S. and Bovik, A.C. (1998). Traffic smoothing for variable bit rate video transmission. *IEEE Transactions on Circuits and Systems for Video Technology*.
167. Lee, S., Pattichis M.S. and Bovik, A.C. (Submitted). Foveated image/video quality assessment and compression gain. *IEEE Transactions on Image Processing*.
168. Pattichis M.S. and Bovik, A.C. (Submitted). Fingerprint recognition using image modulation models. *Pattern Recognition*.
169. Pattichis, M.S., Bovik, A.C. Sidiropoulos, N. and Havlicek, J.W. (Submitted). Searching using sorting. *IEEE Transactions on Image Processing*.
170. Pattichis, M.S., Bovik, A.C. Havlicek J. W. and Sidiropoulos, N.D. (1998). Multidimensional FM transforms with perfect reconstruction. *IEEE Transactions on Image Processing*.

171. Tumer, K., Ramanujam, N., Richards-Kortum, R., and Ghosh, J. (1998). Spectroscopic detection of cervical pre-cancer through radial basis function networks. *IEEE Transactions Biomedical Engineering*, 45(8), 953-961.
172. Sidiropoulos, N., Pattichis, M. S., Bovik, A. C., and Havlicek, J. W. (To appear). COPERM: Transform-domain energy compaction by optimal permutation. *IEEE Transactions on Signal Processing*.
173. Super, B.J. (In preparation). Cluster Selection in Hierarchical Clustering. *Pattern Recognition Journal*.
174. Wei, D. and Bovik, A. C. (1998). Enhancement of compressed images by optimal shift-invariant wavelet packet basis. *Journal of Visual Communication and Image Representation*, Special issue on High-Fidelity Media Processing, 9(1), 15-24.
175. Wei, D. and Bovik, A. C. (To appear). Generalized coiflets with nonzero-centered vanishing moments. *IEEE Transactions on Circuits and Systems II*, Special Issue on Multirate Systems, Filter Banks, Wavelets, and Applications.
176. Wei, D. and Bovik, A. C. (1998). Sampling approximation of smooth functions via generalized coiflets. *IEEE Transactions on Signal Processing*, Special Issue on Theory and Applications of Filter Banks and Wavelets, 46(4), 1133-1998.
177. Wei, D. and Bovik, A. C. (1998). On the instantaneous frequencies of multi-component AM-FM signals. *IEEE Signal Processing Letters*, 5(4), 84-86.
178. Yim, C. and Bovik, A. C. (To appear). Multiresolution 3-D range segmentation using focus cues. *IEEE Transactions on Image Processing*, 8(9).

#### **1998 Conference Presentations / Talks / Technical Reports**

179. Frazor, R.A., Albrecht, D.G., Geisler, W.S. and Crane, A.M. (1998). Discrimination performance of v1 neurons in monkeys and cats for different intervals of integration. *Investigative Ophthalmology & Visual Science Supplement*. (ARVO) 39/4, S238.
180. Gallogly, D.P. and Geisler, W.S. (1998). Contour integration occurs along various stimulus dimensions. *Investigative Ophthalmology & Visual Science Supplement*. (ARVO) 39/4, S847.
181. Havlicek, J. P., Havlicek, J. W., Bovik, A. C., and Mamuya, N. D. (1998). Relating skewed 2-D Hilbert transforms and computed AM-FM models. *IEEE International Conference on Image Processing*, Chicago, IL.

182. Kite, T. D., Damera-Venkata, N., Evans, B. L. and Bovik, A. C. (1998). A high quality, fast inverse halftoning algorithm for error diffused halftones. *IEEE International Conference on Image Processing*, Chicago, IL.
183. Lee, S. and Bovik, A. C. (1998). Maximally flat bandwidth allocation for variable bit rate video. *IEEE International Conference on Image Processing*, Chicago, IL.
184. Lee, S. and Bovik, A. C. (1998). Rate control for foveated MPEG/H.263 video. *IEEE International Conference on Image Processing*, Chicago, IL.
185. Lee, S., Pattichis, M. S. and Bovik, A. C. (1998, October). Foveated image/video quality assessment in curvilinear coordinates. *International Workshop on Very Low Bitrate Video Coding*, Urbana, IL.
186. Thornton, T. and Geisler, W.S. (1998). Texture segregation on the basis of local shape information. *Investigative Ophthalmology & Visual Science Supplement*. (ARVO) 39/4, S649.
187. Tumer, K. (1998). Classifier Combining through Trimmed Means and Order Statistics. *1998 IEEE International Conference on Neural Networks*, Anchorage, Alaska.
188. Wei, D., Pai, H.-T. and Bovik, A. C. (1998). Antisymmetric biorthogonal coiflets for image coding. *IEEE International Conference on Image Processing*, Chicago, IL.

## INVENTIONS / PATENTS

None

## HONORS / AWARDS

- |      |   |
|------|---|
| 1998 | Bovik: Recipient of the IEEE Signal Processing Society Meritorious Service Award.   |
| 1998 | Bovik: Continued as the Editor-in-Chief, <i>IEEE Transactions on Image Processing</i> .   |
| 1998 | Bovik: Named to the Editorial Board of the <i>The Proceedings of the IEEE</i> , which is the main journal of the largest technical/scientific society in the world. |
| 1998 | Bovik: Continued as Member of the Board of Governors of the IEEE Signal Processing Society.   |
| 1998 | 1998 Geisler named Section Editor of Vision Research.   |

- 1998 Ghosh: Plenary Presentation, *SPIE Conf. On Applications and Science of Computational Intelligence*, Orlando.
- 1998 Ghosh appointed Letters Editor, *IEEE Trans. Neural Networks*.
- 1997 Cormack was nominated by the University of Texas for Presidents Young Investigator Award.
- 1997 Ghosh awarded Best Application Paper, Artificial Neural Networks in Engineering (ANNIE'95) Conference, for "Image Enhancement using Scale-based Clustering Properties of the Radial Basis Function Network."
- 1997 Ghosh was keynote speaker, ANNIE'97, St. Louis.
- 1997 Ghosh received Dean's Fellowship, University of Texas.
- 1997 Viswanath Ramamurti, Ph.D completed: "Structurally Adaptation and Generalization in Modular Neural Networks", August, 1997 (Technology Resources Inc (research division of SBC Corp.), Austin)
- 1997 Geisler received one of two campus-wide Career Research Excellence Awards given for the first time this year by the University of Texas at Austin.
- 1995 Geisler named to Editorial Board of Vision Research.
-